



000-41161900 - 01/29/2025 - IAA Inc.





000-41161900 - 01/29/2025 - IAA Inc.



000-41161900 - 01/29/2025 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.

E AND LOADING INFORMATION
INFORMATIONS SUR LES PNEUS ET LE CHARGEMENT

1 CAPACITY 1 TOTAL 1 FRONT 1 REAR
1 DE PLACES 1 TOTAL 5 1 AVANT 2 1 ARRIERE 3

Occupants and cargo should never exceed 420 kg or 925 lbs.
1 et le chargement ne doit jamais dépasser 420 kg ou 925 lb.

	COLD TIRE PRESSURE PRESSION DES PNEUS À FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
7	240 kPa, 35 PSI	
7	240 kPa, 35 PSI	
17	420 kPa, 60 PSI	

51
42561-06B30

MFD. BY: TOYOTA MOTOR MANUFACTURING,
KENTUCKY, INC. 05/20

GVWR 4475LB GAWR FR 2490LB RR 2420LB
THIS VEHICLE CONFORMS TO ALL APPLICABLE
FEDERAL MOTOR VEHICLE SAFETY BUMPER AND
THEFT PREVENTION STANDARDS IN EFFECT ON
THE DATE OF MANUFACTURE SHOWN ABOVE.
4T1C11AK7LU368684 PASS. CAR



C/TR: 040/FA20 AXVA70L-CEZNBA
A/TM: /U880E MADE IN U.S.A. 19112



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.



000-41161900 - 12/20/2024 - IAA Inc.

